

SX24L-6-UTP-BK



SOLARIX CATEGORY 6

Unshielded Patch Panel

2.5/5 Gbps

250 MHz

Number of Ports	24 x RJ45
Life Cycle	1,000 plug insertions
Contact Material	50 pin gold
IDC Block	Dual 110/Krone 8p8c
IDC Block Life Cycle	200 terminations
Conductor Size and Type	AWG 26 - 22, solid
Other Material	FR according to UL94-0
Colour	Black
Units	1U
Height	44 mm
Width	484 mm
Depth	100 mm
Storage Temperature	-40 to +70 °C
Operation Temperature	-10 to +60 °C
Max. Humidity Operation	93 %

Unshielded Solarix Category 6 patch panel with management bar is designed to be used with Solarix Category 6 components as a part of the passive infrastructure solution. The panel meets all electrical parameters specified in the ANSI/TIA 568C.2, ISO/IEC 11801, and EN 50173 standards. It supports both T568A and T568B wiring configurations using an easy to read colour-coded wiring label. Each port of this Solarix Category 6 panel is sequentially numbered for easy administration. The panel is equipped with strain reliefs on the management bar to secure the cables. The Solarix unshielded Category 6 patch panel is equipped with dual 110/Krone termination block and is supplied in black colour (RAL 9005).

Part No.

Description

SX24L-6-UTP-BK

19" Patch Panel Solarix Category 6 UTP 24 x RJ45 with Management Bar Black 1U



SX24L-6-UTP-BK



+420 840 505 555 • info@solarix.cz
www.solarix.cz

