

SOLARIX CATEGORY 5E

Wall Outlets

SX9-2-5E-STP-WH



2.5/5 Gbps

100 MHz

Number of Ports	1 and 2 x RJ45
Life Cycle	1,000 plug insertions
Contact Material	50 µin gold
IDC Block	Krone 8p8c
IDC Block Life Cycle	200 terminations
Conductor Size and Type	AWG 26 - 22, solid
Other Material	FR according to UL94-0
Colour	White
Dimensions	80 x 80 mm
Storage Temperature	-40 to +70 °C
Operation Temperature	-10 to +60 °C
Max. Humidity Operation	93 %

For Solarix Category 5E outlets their high transmission parameters is the key attribute. Two angled RJ45 ports are covered by a plastic frame that fits various trunking systems using 80 x 80 mm modules. The outlets have an excellent performance and they are developed for all demanding markets. Modular construction of these Solarix outlets allows flush mount or wall mount installation using a universal back box. Space for port numbering stickers or direct marking above each port allows an easy administration. All Solarix Category 5E outlets exceed electrical parameters specified in the ANSI/TIA 568C.2, ISO/IEC 11801, and EN 50173 standards. Both T568A and T568B wiring configurations are supported on the Krone termination block.

Part No.

Description

SX9-2-5E-UTP-WH	Wall Outlet Solarix Category 5E UTP 2 x RJ45 White
SX9-2-5E-STP-WH	Wall Outlet Solarix Category 5E STP 2 x RJ45 White
SX9-1-5E-UTP-WH	Wall Outlet Solarix Category 5E UTP 1 x RJ45 White
SX9-1-5E-STP-WH	Wall Outlet Solarix Category 5E STP 1 x RJ45 White
SX9-0-WH	Wall Mounted Back Box 80 x 80 x 40 mm White

SX9-2-5E-UTP-WH



SX9-0-WH



+420 840 505 555 • info@solarix.cz
www.solarix.cz

